

**Head Office:**

Suite 422-470 Granville Street  
Vancouver, B.C., Canada, V6C1V5  
Phone: +1 604.662.3598  
Fax: +1 604.669.6257  
Email: [ngg@telus.net](mailto:ngg@telus.net)

**Australia:**

P.O. Box 7996  
Gold Coast Mail Centre, Qld 9726  
Phone: +61 (7)5592.2274  
Fax: +61 (7)5592.2275  
Email: [info@newguineagold.ca](mailto:info@newguineagold.ca)

Trading Symbols: TSX-V: **NGG**  
Frankfurt: **NG8.FSE**  
Web Site: [www.newguineagold.ca](http://www.newguineagold.ca)

25<sup>th</sup> May 2009

## PRESS RELEASE

### Excellent drill results from Weioko with 34m at 2.76g/t gold including 17m at 4.54g/t gold

Results from the first seven holes of a 15 hole drill program at Weioko Project (Sehulea Property - 100% NGG) all intersected gold mineralisation with best results of 28m at 2.56g/t gold (including a 1m sample of 29.20g/t gold); 34m at 2.76g/t gold (including 3m at 16.27g/t gold); and 16m at 1.19g/t gold. Silver results ranged up to 5m at 11.52g/t silver, including 1m at 35.90g/t. All results are shown in the table below.

Bob McNeil, CEO and Chairman, commented *"These results continue to enhance the value of the Weioko Project which is on Normanby Island, Papua New Guinea, approximately 10kms from NGG's premier project at Imwauna. Any development of Weioko is likely to be co-ordinated with the development of Imwauna. Of interest is the significant silver credit."*

The Weioko Gold Project is a key New Guinea Gold (NGG) gold project that has been partly explored to date but the drilled mineralisation represents less than 5% of the known gold in soil anomalous area (see Press Release dated March 30, 2009).

NGG is presently completing the last hole of a modest 15 diamond core drill program. The results of these holes, when included with results from 20 RC holes and 23 diamond core holes already completed, should be sufficient to allow a resource estimation to be completed in accordance with the guidelines of NI 43-101. The results of all previous holes, using a 0.2g/t gold cut off are shown in Table 1 of the Press Release dated March 30, 2009.

Previous surveys have included soil geochemistry, rock chip, side looking radar and Induced Polarisation (IP) geophysical surveys. Geochemical soil anomalism is present over an area of 6 kms by 2 kms. Only a very small part of this anomalous area has been tested by either drilling or trenching.

## WEIOKO DRILL RESULTS

Hole No	From (m)	To (m)	Length (m)	Gold (g/t)	Silver (g/t)	Cut off Grade (g/t)
PWED35	0	4	4	6.05	8	0.2
including	0	2	2	10.50	10.80	1.0
	8	36	28	2.56	7.13	0.2
including	10	12	2	1.13	5.95	1.0
	15	20	5	7.89	11.52	1.0
including	18	19	1	29.20	35.90	1.0
	23	28	5	3.75	7.62	1.0
including	23	25.5	2.5	5.30	8.90	1.0
	32	34	2	1.22	5.30	1.0
PWED36	0	2	2	2.58	10.70	0.2
	10	22	12	0.89	5.64	0.2
	32	45.3	13.3	0.26	2.70	0.2
PWED37	8	24	16	1.19	7.07	0.2
including	10	11	1	6.06	13.30	1.0
	34	40	6	0.72	4.10	0.2
	51	55	4	0.43	4.40	0.2
	57.5	60.4	2.9	0.28	2.96	0.2
PWED38	0	4	4	1.50	5.25	0.2
including	0	2	2	2.28	4.56	1.0
	10	18	8	1.02	6.40	0.2
including	11	14	3	2.02	7.73	1.0
	22	36	14	1.24	6.63	0.2
including	22	26	4	3.03	8.80	1.0
PWED39	0	2	2	2.47	7.20	0.2
	9	25	16	0.97	6.35	0.2
including	17	21	4	1.70	6.95	1.0
	9	12	3	1.05	5.30	0.2
PWED40	0	3	3	2.15	8.50	0.2
	0	40.5	31.5	0.92	5.33	0.2
including	9	13	4	1.26	4.30	1.0
	17	18	1	4.38	9.80	0.2
	28	29	1	1.24	8	0.2
	31.5	33	1.5	2.47	10.30	0.2
	41	45.4	4.4	1.52	5.28	0.2
including	41	42.5	1.5	3.98	9	1.0
PWED41	9	43	34	2.76	7.71	0.2
including	20	37	17	4.54	9.31	1.0
including	28	31	3	16.27	27.27	1.0
	46	51.4	5.4	0.96	15.18	0.2

## HOLE LOCATION DATA

Hole No	Collar Co-Ordinates		Azimuth (degrees)	Inclination (degrees)	Depth (m)
	Easting (m)	Northing (m)			
PWED035	297600	8895291	183	-43	36
PWED036	297600	8895291	183	-59	45.3
PWED037	297600	8895291	180	-70	60.4
PWED038	297600	8895291	064	-43	36
PWED039	297600	8895291	089	-61	45.4
PWED040	297600	8895291	150	-44	40.5
PWED041	297600	8895291	148	-60	51.4

**Note:** The true thickness of the above intersections cannot be determined until a resource model is completed.

Drill core is logged and split (all by saw) on site with half core being dispatched to, and assayed by accredited laboratory ALS-Chemex in Townsville, Australia. In house and laboratory standards are used for quality control plus regular check sample assaying.

The information in this release was prepared under the direction of Robert D. McNeil a Fellow of the Australia Institute of Mines and Metallurgy and a "qualified person" as defined by National Instrument 43-101. Mr McNeil has read and approves the information contained herein.

Full details of the Sinivit Project are described in an Independent N1 43-101 report dated January 2006 which is available at [www.newguineagold.ca](http://www.newguineagold.ca).

For further information on this release or on other NGG projects such as the Sinivit Gold Mine, contact Forbes West toll free at 888 655 5532, email [forbes@sherbournegroup.ca](mailto:forbes@sherbournegroup.ca) or Judith O'Quinn at 604 662 3598, email [ngg@telus.net](mailto:ngg@telus.net) or access our website - [www.newguineagold.ca](http://www.newguineagold.ca)

**ON BEHALF OF THE BOARD**

R.D.McNeil

**CHAIRMAN & CEO**

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.